


Lecture 7 - Sparse Iteration Model I


Stanford CS343D (Fall 2021)
Fred Kjolstad

Course Project



Each person contributes one pitch slide to a google slide deck.
These pitches are not binding.

Lecture Overview



Overview of topics

Lecture 7

- Data representation
- Iteration spaces
- Iteration graph IR
- Iteration lattices to represent coiteration

Lecture 8

- Concrete index notation IR
- Code generation algorithm
- Derived iteration spaces
- Optimizing transformations

Sparse Tensor Algebra Compilation

Tensor Expression

$$\begin{array}{lll} A = Bc + a & a = Bc \\ A = B \odot C & A = B + C & a = \alpha Bc + \beta a \\ A = BCd & A = \alpha B & A = 0 \quad A = BC \\ A_{ij} = \sum_{kl} B_{ikl} C_{lj} D_{kj} & A_{ik} = \sum_j B_{ijk} c_j & A_{kj} = \sum_{il} B_{ikl} C_{lj} D_{ij} \\ A_{ijk} = \sum_l B_{ikl} C_{lj} & A_{ij} = (\sum_k B_{ijk} C_{ijk}) + D_{ij} \\ C = \sum_{ijkl} M_{ij} P_{jk} \overline{M_{lk}} \overline{P_{il}} & \tau = \sum_i z_i (\sum_j z_j \theta_{ij}) (\sum_k z_k \theta_{ik}) \\ a = \sum_{ijklmno} M_{ij} P_{jk} M_{kl} P_{lm} \overline{M_{nm}} P_{no} \overline{M_{po}} \overline{P_{ip}} \end{array}$$


Formats

Dense Matrix	CSR	BCSR
COO	DCSR	ELLPACK
DIA	Blocked COO	CSB
Blocked DIA	DCSC	CSC
Sparse vector	Hash Maps	
CSF	Dense Tensors	
Blocked Tensors		

Schedule

reorder
split
precompute
unroll
collapse
parallelize

Sparse Tensor Algebra Compiler (taco)



THE
C
PROGRAMMING
LANGUAGE




DSAs



(work in progress)


Tensor index notation for expressing functionality

$$A_{ij} = B_{ij} + C_{ij}$$




element-wise

$$\alpha = \sum_i b_i c_i$$



reduction over i


$$a_i = \sum_j B_{ij} c_j$$



broadcast c_j over i

Generates fast code for any tensor index notation expression with the given formats and schedule



$$\begin{aligned}
 & a = Bc \\
 & a = Bc + a \\
 & a = Bc + b \quad A = B + C \quad a = \alpha Bc + \beta a \\
 & \quad a = B^T c \quad A = \alpha B \quad a = B(c + d) \\
 & a = B^T c + d \quad A = B + C + D \quad A = BC \\
 & A = B \odot C \quad a = b \odot c \quad A = 0 \quad A = B \odot (CD) \\
 & \quad A = BCd \quad A = B^T \quad a = B^T Bc \\
 & a = b + c \quad A = B \quad K = A^T CA \\
 & A_{ij} = \sum_{kl} B_{ikl} C_{lj} D_{kj} \quad A_{kj} = \sum_{il} B_{ikl} C_{lj} D_{ij} \\
 & \quad A_{lj} = \sum_{ik} B_{ikl} C_{ij} D_{kj} \quad A_{ij} = \sum_k B_{ijk} c_k \\
 & A_{ijk} = \sum_l B_{ikl} C_{lj} \quad A_{ik} = \sum_j B_{ijk} c_j \\
 & \quad A_{jk} = \sum_i B_{ijk} c_i \quad A_{ijl} = \sum_k B_{ikl} C_{kj} \\
 & C = \sum_{ijkl} M_{ij} P_{jk} \overline{M_{lk}} \overline{P_{il}} \quad \tau = \sum_i z_i (\sum_j z_j \theta_{ij}) (\sum_k z_k \theta_{ik}) \\
 & \quad a = \sum_{ijklmnop} M_{ij} P_{jk} M_{kl} P_{lm} \overline{M_{nm}} P_{no} \overline{M_{po}} \overline{P_{ip}}
 \end{aligned}$$



Dense Matrix				
CSR	DCSR	BCSR		
COO	ELLPACK	CSB	CPU	
Blocked COO		CSC	GPUs	TPUs
DIA	Blocked DIA	DCSC	FPGA	
Sparse vector		Hash Maps		Sparse Tensor Hardware
Coordinates				
CSF		Dense Tensors		Cloud Computers
		Blocked Tensors		Supercomputers
Linked Lists		Database		
Compression Schemes				
Cloud Storage				

Compound expressions matter for performance

$$A = B \odot (CD)$$




Unfused: $\Theta(n^2k)$

Fused: $\Theta(\text{nnz}_B \cdot k)$

Formats matter for performance

Dense Matrix



Formats

Best performance

Dense

List of Rows

CSR

DCSR

$$y = Ax$$



Normalized time

Formats matter for performance


Thermal Matrix



Formats


- Best performance
- CSR
 - DCSR
 - Dense
 - List of Rows

$$y = Ax$$



Formats matter for performance


Row-sliced Matrix



Formats


Best performance
List of Rows
DCSR
CSR
Dense

$$y = Ax$$



Formats matter for performance

Hypersparse Matrix



Formats

Best performance


DCSR

CSR


List of Rows

Dense

$$y = Ax$$




CSR vs COO



Schedules matter for performance


$$y = Ax \text{ (CPU)}$$




Machines matter for performance

$$a_i = \sum_j B_{ij} c_j \quad (\text{SpMV})$$

CPU



GPU




Sparse data structures in graphs, tensors, and relations encode coordinates in a sparse iteration space



Tensor (nonzeros)		Relation (rows)	Graph (edges)
	(0,1)	(Harry,CS)	(v ₁ ,v ₅)
(2,3)	(0,5)	(Sally,EE)	(v ₄ ,v ₃)
(5,5)	(7,5)	(George,CS)	(v ₅ ,v ₃)
		(Rita,CS)	(v ₃ ,v ₅)
		(Mary,ME)	(v ₃ ,v ₁)

Values may be attached to these coordinates: e.g., nonzero values, edge attributes


Iteration spaces from coordinate relations






Iteration spaces from set operations




=






\cap




=





\cup



=





\cup




\cap

Iteration spaces from broadcast operations



$$A_{ij} = \sum_k B_{ik} C_{kj}$$

$$B_{ik} \cap C_{kj}$$



The universe of i consist of all coordinates it may take, of which any data structure stores a subset.

Coordinate relations → coordinate trees (abstractly)


Matrix

	j_1	j_2	j_3
i_1	a	b	
i_2		e	
i_3	g	h	i


Coordinate Relation

$$\begin{array}{ll} (i_1, j_1) \rightarrow a & (i_1, j_2) \rightarrow b \\ (i_3, j_3) \rightarrow i & (i_2, j_2) \rightarrow e \\ (i_3, j_1) \rightarrow g & \\ (i_3, j_2) \rightarrow h & \end{array}$$



Coordinate Tree



Coordinate relations → coordinate trees (concretely)



Coordinate relations → coordinate trees (concretely)



Coordinate relations → coordinate trees (concretely)

row(3) = ???
col(3) = ???

	0		2	3
0	A		B	
		C	D	E
2				F



Coordinate relations → coordinate trees (concretely)

Coordinate

	rows					
	0	0	1	1	1	2

cols	0	2	1	2	3	3
------	---	---	---	---	---	---



0	A		B	
1		C	D	E
2				F

Coordinate relations → coordinate trees (concretely)

Coordinate

	Coordinate					
rows	0	0	1	1	1	2
cols	0	2	1	2	3	3

0	I	2	3
A		B	
	C	D	E
2			F



Coordinate relations → coordinate trees (concretely)




		Coordinate			Duplicates
		rows	0	1	2
cols	0	0	1	1	2

0		2	3
A		B	
C	D	E	




Coordinate relations → coordinate trees (concretely)

Compressed Sparse Rows (CSR)




Level-based representation













Level abstraction: capabilities and properties

Capabilities



Properties



The code generator sees only the level abstraction and not specific level types

Level types: dense and compressed

Dense locate capability:

```
locate(pk-1, i1, ..., ik):  
    return <pk-1 * Nk + ik, true>
```

Compressed iterate capability

```
pos_bounds(pk-1):  
    return <pos[pk-1], pos[pk-1 + 1]>
```

```
pos_access(pk, i1, ..., ik-1):  
    return <crd[pk], true>
```

$$y = Ax$$

```
for (int i = 0; i < m; i++) {  
    for (int pA = A_pos[i]; pA < A_pos[i+1]; pA++) {  
        int j = A_crd[pA];  
        y[i] += A[pA] * x[j];  
    }  
}
```

Level types: dense and compressed

Dense locate capability:

```
locate(pk-1, i1, ..., ik):  
    return <pk-1 * Nk + ik, true>
```

Compressed iterate capability

$$y = Ax$$

```
for (int i = 0; i < m; i++) {  
    for (int pA = A_pos[i]; pA < A_pos[i+1]; pA++) {  
        int j = A_crd[pA];  
        y[i] += A[pA] * x[j];  
    }  
}
```

```
pos_bounds(pk-1):  
    return <pos[pk-1], pos[pk-1 + 1]>  
  
pos_access(pk, i1, ..., ik-1):  
    return <crd[pk], true>
```

Compressed iterate

Level types: dense and compressed

Dense locate capability:

```
locate(pk-1, i1, ..., ik):  
    return <pk-1 * Nk + ik, true>
```

Compressed iterate capability

$$y = Ax$$

```
for (int i = 0; i < m; i++) {  
    for (int pA = A_pos[i]; pA < A_pos[i+1]; pA++) {  
        int j = A_crd[pA];  
        y[i] += A[pA] * x[j];  
    }  
}
```

```
pos_bounds(pk-1):  
    return <pos[pk-1], pos[pk-1 + 1]>  
  
pos_access(pk, i1, ..., ik-1):  
    return <crd[pk], true>
```

Compressed iterate

Level types: dense and compressed

Dense locate capability:

```
locate(pk-1, i1, ..., ik):  
    return <pk-1 * Nk + ik, true>
```

Compressed iterate capability

```
pos_bounds(pk-1):  
    return <pos[pk-1], pos[pk-1 + 1]>
```

```
pos_access(pk, i1, ..., ik-1):  
    return <crd[pk], true>
```

$$y = Ax$$

```
for (int i = 0; i < m; i++) {  
    for (int pA = A_pos[i]; pA < A_pos[i+1]; pA++) {  
        int j = A_crd[pA];  
        y[i] += A[pA] * x[j];  
    }  
}
```

Dense locate


Compressed iterate

Level types can be composed in many ways

Dense




Compressed




Singleton




Dense




Compressed




Level types can be composed in many ways



Level types can be composed in many ways



Level types can be composed in many ways




Level types can be composed in many ways

Tensor formats	Level formats	Dense	Compressed	Singleton
		Hashed	Range	Offset
Coordinate matrix	CSR	Dense	Dense array tensor	Coordinate tensor
	Compressed	Dense	Dense	Compressed
	Singleton	Compressed	Dense	Singleton
	[Tinney and Walker, 1967]		Dense	Singleton
Mode-generic tensor	BCSR	Dense	CSB	ELLPACK
	Compressed	Dense	Dense	Dense
	Singletton	Compressed	Compressed	Dense
	Dense	Dense	Dense	Singletton
	[Baskaran et al. 2012]	Dense	Singletton	[Kincaid et al. 1989]
Hash map vector	Hash map matrix	DIA	Block DIA	
	Hashed	Dense	Dense	Dense
	[Patwary et al. 2015]	Range	Range	Range
Hash map matrix	Hash map matrix	Offset	Offset	Offset
	Hashed	Dense	Dense	Dense
	Hashed	Range	Range	Range
	[Saad 2003]	Offset	Offset	Offset


Iteration graphs express iteration spaces and data structure ordering

Iteration Space




B_{ijk}

Coordinate Tree



Iteration Graph




$\forall_i \forall_j \forall_k B_{ijk}$

30 40 50 10 70 80 20 60


Sparse iteration spaces and Iteration Graphs

$$A_{ij} = \sum_k B_{ijk} * c_k$$



Sparse iteration spaces and Iteration Graphs

$$A_{ij} = \sum_k B_{ijk} * C_k$$



Sparse iteration spaces and Iteration Graphs

$$A_{ij} = \sum_k B_{ijk} * C_k$$

B _{ijk} * C _k			
i	j	k	
		30	0
		0	120
		0	0
		0	0
		0	0
		10	210
		0	60

Dense

Sparse iteration spaces and Iteration Graphs

$$A_{ij} = \sum_k B_{ijk} * C_k$$

B_{ijk}

	30			40	50
i					
j	10			70	
		80	20	60	
k					

C_k

1			3	
1			3	
1			3	
1			3	
1			3	

$B_{ijk} * C_k$


30	0	120	0
0	0	0	0
0	0	0	0
10	0	210	0
0	0	60	0

Sparse

Dense


Sparse iteration spaces and Iteration Graphs

$$A_{ij} = \sum_k B_{ijk} * C_k$$




Sparse iteration spaces and Iteration Graphs

$$A_{ij} = \sum_k B_{ijk} * C_k$$





Sparse iteration spaces and Iteration Graphs

$$A_{ij} = \sum_k B_{ijk} * C_k$$




Sparse iteration spaces and Iteration Graphs


$$A_{ij} = \sum_k B_{ijk} * C_k$$




Iteration graph examples




$$\frac{\forall_i \ b_i \cap c_i}{i \in b_1 \cap c_1}$$




$$\frac{\forall_i \forall_j \forall_k \ B_{ijk} \cup C_{ijk}}{i \in B_1 \cup C_1 \\ j \in B_2 \cup C_2 \\ k \in B_3 \cup C_3}$$



$$\frac{\forall_i \forall_j (B_{ij} \cup C_{ij}) \cap D_{ij}}{i \in (B_1 \cup C_1) \cap D_1 \\ j \in (B_2 \cup C_2) \cap D_2}$$




$$\frac{\forall_i \forall_j B_{ij} \cap c_j}{i \in B_1 \cap \mathbb{U}_i \\ j \in B_2 \cap c_1}$$




$$\frac{\forall_i \alpha \cup b_i}{i \in \mathbb{U}_i \cap b_1}$$

$$\frac{\forall_i \forall_k \forall_j B_{ik} \cap C_{kj}}{i \in B_1 \cap \mathbb{U}_i \\ k \in B_2 \cap C_1 \\ j \in \mathbb{U}_j \cap C_2}$$




$$\frac{\forall_i \forall_k \forall_l \forall_j B_{ikl} \cap C_{kj} \cap D_{lj}}{i \in B_1 \cap \mathbb{U}_i \cap \mathbb{U}_i \\ k \in B_2 \cap C_1 \cap \mathbb{U}_k \\ l \in B_3 \cap \mathbb{U}_l \cap D_1 \\ j \in \mathbb{U}_j \cap C_2 \cap D_2}$$



$$\frac{\forall_i (\forall_j B_{ij} \cap c_j) \cup d_i}{i \in (B_1 \cap \mathbb{U}_i) \cup d_1 \\ j \in B_2 \cap c_1}$$


Iteration graphs are lowered to sparse code

$$A_{ij} = \sum_k B_{ijk} c_k$$




Iteration graphs are lowered to sparse code

$$A_{ij} = \sum_k B_{ijk} c_k$$




Iteration graphs are lowered to sparse code

$$A_{ij} = \sum_k B_{ijk} c_k$$





Data structure coiteration

Coordinate Space




Data structure coiteration

Coordinate Space



Data structure coiteration

Coordinate Space



Data structure coiteration

Coordinate Space



$$b \times c$$



Matrix b :

0	
1	
4	
6	
7	

Matrix c :



0	
2	
4	

Data structure coiteration





Data structure coiteration

Coordinate Space





Data structure coiteration

Coordinate Space





Data structure coiteration

Coordinate Space





Data structure coiteration

Coordinate Space





Data structure coiteration

Coordinate Space





Data structure coiteration

Coordinate Space




Data structure coiteration

Coordinate Space



Data structure coiteration

Coordinate Space





$$a = \begin{array}{c|c} 0 & \text{blue} \\ 1 & \text{white} \\ 2 & \text{white} \\ 3 & \text{white} \\ 4 & \text{blue} \\ 5 & \text{white} \\ 6 & \text{white} \\ 7 & \text{blue} \end{array} \quad b = \begin{array}{c|c} 0 & \text{white} \\ 1 & \text{white} \\ 4 & \text{white} \\ 6 & \text{gray} \\ 7 & \text{blue} \end{array} \quad c = \begin{array}{c|c} 0 & \text{white} \\ 2 & \text{white} \\ 4 & \text{white} \\ 6 & \text{white} \\ 7 & \text{light green} \end{array}$$

$a = b \cup c$


Data structure coiteration

Coordinate Space



Data structure coiteration

Coordinate Space



$$a = \begin{array}{c} 0 \\ 1 \\ 2 \\ 3 \\ 4 \\ 5 \\ 6 \\ 7 \end{array} \quad b = \begin{array}{c} 0 \\ 1 \\ 4 \\ 6 \\ 7 \end{array} \quad c = \begin{array}{c} 0 \\ 2 \\ 4 \end{array}$$


a b c

$=$

\cup


Data structure coiteration

Coordinate Space




$$a = \left(\begin{array}{c|c} \text{b} & \\ \hline 0 & \\ 1 & \\ 2 & \\ 3 & \\ 4 & \text{b} \\ 5 & \\ 6 & \\ 7 & \end{array} \right) \cup \left(\begin{array}{c|c} \text{c} & \\ \hline 0 & \\ 2 & \\ 4 & \text{c} \\ 6 & \\ 7 & \end{array} \right) \cap \left(\begin{array}{c|c} \text{d} & \\ \hline 3 & \\ 4 & \\ 7 & \text{d} \end{array} \right)$$


Coiteration successively eliminates data structures



Coiterate over regions with b , c , and d



b runs out of values




c runs out of values

Iteration lattice for multiplications

$$a_i = b_i c_i$$

Iteration lattice for multiplications





$$a_i = b_i c_i$$

Multiplication requires intersection

$$b \cap c$$



Iteration lattice for multiplications

$$a_i = b_i c_i$$





Iteration lattice for multiplications

$$a_i = b_i c_i$$



Iteration lattice for multiplications

$$a_i = b_i c_i$$





```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int i = min(ib, ic);

    if (ib == i) pb1++;
    if (ic == i) pc1++;
}
```

Iteration lattice for multiplications



$$a_i = b_i c_i$$



```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int i = min(ib, ic);
    if (ib == i && ic == i) {
        a[i] = b[pb1] * c[pc1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
}
```

Iteration lattice for multiplications

$$a_i = b_i c_i$$




```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int i = min(ib, ic);
    if (ib == i && ic == i) {
        a[i] = b[pb1] * c[pc1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
}
```

Iteration lattice for additions

$$a_i = b_i + c_i$$

Iteration lattice for additions




$$a_i = b_i + c_i$$

Addition requires union


Iteration lattice for additions

$$a_i = b_i + c_i$$



Iteration lattice for additions



$$a_i = b_i + c_i$$



$$b \cup c = (b \cap c) \cup b \cup c$$



Iteration lattice for additions

$$a_i = b_i + c_i$$





Iteration lattice for additions

$$a_i = b_i + c_i$$



Iteration lattice for additions

$$a_i = b_i + c_i$$





```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int i = min(ib, ic);

    if (ib == i) pb1++;
    if (ic == i) pc1++;
}
```

Iteration lattice for additions



$$a_i = b_i + c_i$$



```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int i = min(ib, ic);
    if (ib == i && ic == i) {
        a[i] = b[pb1] + c[pc1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
}
```

Iteration lattice for additions



$$a_i = b_i + c_i$$



```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int i = min(ib, ic);
    if (ib == i && ic == i) {
        a[i] = b[pb1] + c[pc1];
    } else if (ib == i) {
        a[i] = b[pb1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
}
```

Iteration lattice for additions



$$a_i = b_i + c_i$$



```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int i = min(ib, ic);
    if (ib == i && ic == i) {
        a[i] = b[pb1] + c[pc1];
    }
    else if (ib == i) {
        a[i] = b[pb1];
    }
    else {
        a[i] = c[pc1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
}
```

Iteration lattice for additions



$$a_i = b_i + c_i$$



```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int i = min(ib, ic);
    if (ib == i && ic == i) {
        a[i] = b[pb1] + c[pc1];
    }
    else if (ib == i) {
        a[i] = b[pb1];
    }
    else {
        a[i] = c[pc1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
}
```

Iteration lattice for additions

$$a_i = b_i + c_i$$





```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int i = min(ib, ic);
    if (ib == i && ic == i) {
        a[i] = b[pb1] + c[pc1];
    }
    else if (ib == i) {
        a[i] = b[pb1];
    }
    else {
        a[i] = c[pc1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
}

while (pb1 < b1_pos[1]) {
    int i = b1_crd[pb1];
    a[i] = b[pb1++];
}
```

Iteration lattice for additions

$$a_i = b_i + c_i$$





```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int i = min(ib, ic);
    if (ib == i && ic == i) {
        a[i] = b[pb1] + c[pc1];
    }
    else if (ib == i) {
        a[i] = b[pb1];
    }
    else {
        a[i] = c[pc1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
}

while (pb1 < b1_pos[1]) {
    int i = b1_crd[pb1];
    a[i] = b[pb1++];
}

while (pc1 < c1_pos[1]) {
    int i = c1_crd[pc1];
    a[i] = c[pc1++];
}
```



Iteration lattice for a compound expression

$$a_i = b_i + c_i + d_i$$



Iteration lattice for a compound expression

$$a_i = b_i + c_i + d_i$$



```

int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
int pd1 = d1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ib, ic, id);
    if (ic == i && id == i) {
        a[i] = c[pc1] + d[pd1];
    } else if (ic == i) {
        a[i] = c[pc1];
    } else {
        a[i] = d[pd1];
    }
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pb1 < b1_pos[1] && pd1 < d1_pos[1]) {
    int ib = b1_crd[pb1];
    int id = d1_crd[pd1];
    int i = min(ib, id);
    if (ib == i && id == i) {
        a[i] = b[pb1] + d[pd1];
    } else if (ib == i) {
        a[i] = b[pb1];
    } else if (id == i) {
        a[i] = d[pd1];
    }
    if (ib == i) pb1++;
    if (id == i) pd1++;
}

while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int i = min(ib, ic);
    if (ib == i && ic == i) {
        a[i] = b[pb1] + c[pc1];
    } else if (ib == i) {
        a[i] = b[pb1];
    } else {
        a[i] = c[pc1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
}

while (pd1 < d1_pos[1]) {
    int id = d1_crd[pd1];
    a[id] = d[pd1];
    pd1++;
}



while (pb1 < b1_pos[1]) {
    int ib = b1_crd[pb1];
    a[ib] = b[pb1];
    pb1++;
}

while (pc1 < c1_pos[1]) {
    int ic = c1_crd[pc1];
    a[ic] = c[pc1];
    pc1++;
}

while (pb1 < b1_pos[1]) {
    int ib = b1_crd[pb1];
    a[ib] = b[pb1];
    pb1++;
}
  
```

Iteration lattice for a compound expression

$$a_i = b_i + c_i + d_i \quad \text{Dense}$$



```

int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
int pd1 = d1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ib, ic, id);
    if (ib == i && id == i) {
        a[i] = c[pc1] + d[pd1];
    } else if (ic == i && id == i) {
        a[i] = b[pb1];
    } else {
        a[i] = d[pd1];
    }
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pb1 < b1_pos[1] && pd1 < d1_pos[1]) {
    int ib = b1_crd[pb1];
    int id = d1_crd[pd1];
    int i = min(ib, id);
    if (ib == i && id == i) {
        a[i] = b[pb1] + d[pd1];
    } else if (ib == i) {
        a[i] = b[pb1];
    } else {
        a[i] = d[pd1];
    }
    if (ib == i) pb1++;
    if (id == i) pd1++;
}

while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int i = min(ib, ic);
    if (ib == i && ic == i) {
        a[i] = b[pb1] + c[pc1];
    } else if (ib == i) {
        a[i] = b[pb1];
    } else {
        a[i] = c[pc1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
}

while (pd1 < d1_pos[1]) {
    int id = d1_crd[pd1];
    a[id] = d[pd1];
    pd1++;
}

while (pb1 < b1_pos[1]) {
    int ib = b1_crd[pb1];
    a[ib] = b[pb1];
    pb1++;
}



while (pc1 < c1_pos[1]) {
    int ic = c1_crd[pc1];
    a[ic] = c[pc1];
    pc1++;
}

while (pb1 < b1_pos[1]) {
    int ib = b1_crd[pb1];
    a[ib] = b[pb1];
    pb1++;
}

```

Iteration lattice for a compound expression

$$a_i = b_i + c_i + d_i \quad \text{Dense}$$



```

int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
int id = 0;
while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int pd1 = id;
    int pa1 = id;
    if (ic == id) {
        a[pa1] = c[pc1] + d[pd1];
    } else {
        a[pa1] = d[pd1];
    }
    if (ib == id && ic == id) {
        a[pa1] = b[pb1] + c[pc1] + d[pd1];
    } else if (ib == id) {
        a[pa1] = b[pb1] + d[pd1];
    } else if (ic == id) {
        a[pa1] = c[pc1] + d[pd1];
    } else {
        a[pa1] = d[pd1];
    }
    if (ib == id) pb1++;
    if (ic == id) pc1++;
    id++;
}



while (pb1 < b1_pos[1]) {
    int ib = b1_crd[pb1];
    int pd1 = id;
    int pa1 = id;
    if (ib == id) {
        a[pa1] = b[pb1] + d[pd1];
    } else {
        a[pa1] = d[pd1];
    }
    if (ib == id) pb1++;
    id++;
}

while (id < d1_dimension) {
    int pd1 = id;
    int pa1 = id;
    a[pa1] = d[pd1];
    id++;
}

```



Iteration lattice for a compound expression

$$a_i = (b_i + c_i)d_i$$



Iteration lattice for a compound expression

$$a_i = (b_i + c_i)d_i$$





```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
int pd1 = d1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ib, ic, id);
    if (ib == i && ic == i && id == i) {
        a[i] = (b[pb1] + c[pc1]) * d[pd1];
    } else if (ib == i && id == i) {
        a[i] = b[pb1] * d[pd1];
    } else if (ic == i && id == i) {
        a[i] = c[pc1] * d[pd1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ic, id);
    if (ic == i && id == i) {
        a[i] = c[pc1] * d[pd1];
    }
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pb1 < b1_pos[1] && pd1 < d1_pos[1])
{
    int ib = b1_crd[pb1];
    int id = d1_crd[pd1];
    int i = min(ib, id);
    if (ib == i && id == i) {
        a[i] = b[pb1] * d[pd1];
    }
    if (ib == i) pb1++;
    if (id == i) pd1++;
}
```

Iteration lattice for a compound expression

$$a_i = (b_i + c_i)d_i \quad \text{Dense}$$





```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
int pd1 = d1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ib, ic, id);
    if (ib == i && ic == i && id == i) {
        a[i] = (b[pb1] + c[pc1]) * d[pd1];
    } else if (ib == i && id == i) {
        a[i] = b[pb1] * d[pd1];
    } else if (ic == i && id == i) {
        a[i] = c[pc1] * d[pd1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ic, id);
    if (ic == i && id == i) {
        a[i] = c[pc1] * d[pd1];
    }
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pb1 < b1_pos[1] && pd1 < d1_pos[1])
{
    int ib = b1_crd[pb1];
    int id = d1_crd[pd1];
    int i = min(ib, id);
    if (ib == i && id == i) {
        a[i] = b[pb1] * d[pd1];
    }
    if (ib == i) pb1++;
    if (id == i) pd1++;
}
```

Iteration lattice for a compound expression

$$a_i = (b_i + c_i)d_i \quad \text{Dense}$$





```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
int pd1 = d1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ib, ic, id);
    if (ib == i && ic == i && id == i) {
        a[i] = (b[pb1] + c[pc1]) * d[pd1];
    } else if (ib == i && id == i) {
        a[i] = b[pb1] * d[pd1];
    } else if (ic == i && id == i) {
        a[i] = c[pc1] * d[pd1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ic, id);
    if (ic == i && id == i) {
        a[i] = c[pc1] * d[pd1];
    }
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pb1 < b1_pos[1] && pd1 < d1_pos[1])
{
    int ib = b1_crd[pb1];
    int id = d1_crd[pd1];
    int i = min(ib, id);
    if (ib == i && id == i) {
        a[i] = b[pb1] * d[pd1];
    }
    if (ib == i) pb1++;
    if (id == i) pd1++;
}
```

Iteration lattice for a compound expression

$$a_i = (b_i + c_i)d_i \quad \text{Dense}$$





```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
int pd1 = d1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ib, ic, id);
    if (ib == i && ic == i && id == i) {
        a[i] = (b[pb1] + c[pc1]) * d[pd1];
    } else if (ib == i && id == i) {
        a[i] = b[pb1] * d[pd1];
    } else if (ic == i && id == i) {
        a[i] = c[pc1] * d[pd1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ic, id);
    if (ic == i && id == i) {
        a[i] = c[pc1] * d[pd1];
    }
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pb1 < b1_pos[1] && pd1 < d1_pos[1])
{
    int ib = b1_crd[pb1];
    int id = d1_crd[pd1];
    int i = min(ib, id);
    if (ib == i && id == i) {
        a[i] = b[pb1] * d[pd1];
    }
    if (ib == i) pb1++;
    if (id == i) pd1++;
}
```

Iteration lattice for a compound expression

$$a_i = (b_i + c_i)d_i \quad \text{Dense}$$





```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
int pd1 = d1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ib, ic, id);
    if (ib == i && ic == i && id == i) {
        a[i] = (b[pb1] + c[pc1]) * d[pd1];
    } else if (ib == i && id == i) {
        a[i] = b[pb1] * d[pd1];
    } else if (ic == i && id == i) {
        a[i] = c[pc1] * d[pd1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ic, id);
    if (ic == i && id == i) {
        a[i] = c[pc1] * d[pd1];
    }
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pb1 < b1_pos[1] && pd1 < d1_pos[1])
{
    int ib = b1_crd[pb1];
    int id = d1_crd[pd1];
    int i = min(ib, id);
    if (ib == i && id == i) {
        a[i] = b[pb1] * d[pd1];
    }
    if (ib == i) pb1++;
    if (id == i) pd1++;
}
```

Iteration lattice for a compound expression

$$a_i = (b_i + c_i)d_i \quad \text{Dense}$$





```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
int pd1 = d1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ib, ic, id);
    if (ib == i && ic == i && id == i) {
        a[i] = (b[pb1] + c[pc1]) * d[pd1];
    } else if (ib == i && id == i) {
        a[i] = b[pb1] * d[pd1];
    } else if (ic == i && id == i) {
        a[i] = c[pc1] * d[pd1];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pc1 < c1_pos[1] && pd1 < d1_pos[1]) {
    int ic = c1_crd[pc1];
    int id = d1_crd[pd1];
    int i = min(ic, id);
    if (ic == i && id == i) {
        a[i] = c[pc1] * d[pd1];
    }
    if (ic == i) pc1++;
    if (id == i) pd1++;
}

while (pb1 < b1_pos[1] && pd1 < d1_pos[1])
{
    int ib = b1_crd[pb1];
    int id = d1_crd[pd1];
    int i = min(ib, id);
    if (ib == i && id == i) {
        a[i] = b[pb1] * d[pd1];
    }
    if (ib == i) pb1++;
    if (id == i) pd1++;
}
```

Iteration lattice for a compound expression

$$a_i = (b_i + c_i)d_i \quad \text{Dense}$$




```
int pb1 = b1_pos[0];
int pc1 = c1_pos[0];
while (pb1 < b1_pos[1] && pc1 < c1_pos[1]) {
    int ib = b1_crd[pb1];
    int ic = c1_crd[pc1];
    int i = min(ib, ic);
    if (ib == i && ic == i) {
        a[i] = (b[pb1] + c[pc1]) * d[i];
    }
    else if (ib == i) {
        a[i] = b[pb1] * d[i];
    }
    else if (ic == i) {
        a[i] = c[pc1] * d[i];
    }
    if (ib == i) pb1++;
    if (ic == i) pc1++;
}


while (pb1 < b1_pos[1]) {
    int i = b1_crd[pb1];
    a[i] = b[pb1] * d[i];
    pb1++;
}

while (pc1 < c1_pos[1]) {
    int i = c1_crd[pc1];
    a[i] = c[pc1] * d[i];
    pc1++;
}
```


Iteration lattice construction




Bottom-up construction from set expression:
create and merge iteration lattices



b has an iterator



b does not have an iterator,
but supports locate



b is the set universe


Lattice point merging:

$$((b, c), (d, e)) \rightarrow (b, c, d, e)$$

Lattice points are merged by
taking the union of their iterator
and locator sets respectively


Iteration lattice construction

Intersection



The intersection of two lattices is computed by merging the lattice point pairs in the Cartesian combination of their lattice points.



Iteration lattice construction



The union of two lattices is computed by first merging the lattice point pairs in the Cartesian combination of their lattice points. The union of the lattices is then the union of the result and the two initial lattices.

Iteration lattice optimization example

Intersection Optimization



When intersecting two lattices, move the operands with the locate capability from one side of the intersection from the iterators to the locators set.

Lecture Overview

