

Lecture 15 — Domain Specific Accelerators

Stanford CS343D (Winter 2023)

Fred Kjolstad

Domain-Specific Software Stack

Domain-Specific Language/Library

Domain-Specific Compiler

Domain-Specific Hardware

Why Domain-Specific Architectures


Chip type:

Microprocessor


Microprocessor + GPU

General purpose DSP

Dedicated design



Hardware in Industry




Types of Hardware

Multicore CPUs




SIMT GPUs



Fixed-Function ASICs

SIMD




Programmable Streaming Dataflow

CGRA

RDA

Economics of Hardware



Economics of Hardware

“That changed in 2013 when a projection showed people searching by voice for three minutes a day using speech recognition DNNs would double our datacenters’ computation demands, which would be very expensive using conventional CPUs.”


Hardware Design Considerations

Integer	
Add	
8 bit	0.03pJ
32 bit	0.1pJ
Mult	
8 bit	0.2pJ
32 bit	3.1pJ

FP	
FAdd	
16 bit	0.4pJ
32 bit	0.9pJ
FMult	
16 bit	1.1pJ
32 bit	3.7pJ


Memory	
Cache	(64bit)
8KB	10pJ
32KB	20pJ
1MB	100pJ
DRAM	1.3-2.6nJ

Instruction Energy Breakdown




Spatial Hardware (a.k.a. streaming dataflow hardware)


von Neumann architecture



Spatial architecture



Overview: Sparse Tensor Algebra Compilation





Hardware design for general sparse tensor operations

Sparse tensor algebra accelerators must support:

1. **Generality:** arbitrary tensor algebra operations
2. **Data Structures:** dense and sparse data structures
3. **Fusion:** Fusion across operations
4. **Reordering:** Changing the order they process tensor dimensions

Abstract tensor data model




(0, 1, 3)


((1), (0, 2), (1, 3))

((1), (2, 3), (4, 5))

Tensors on Wires




Sparse-matrix sparse-matrix multiplication




$$\forall_i \forall_k \forall_j X_{ij} + = B_{ik} * C_{kj}$$

Streaming dataflow abstract machine (for sparse tensor algebra)


Hierarchical Iteration




Broadcasting



Coiteration / Locate





Computation / Reduction



Compiling to the streaming dataflow abstract machine

$$\forall_i \in B_i \cap U_i$$




$$\forall_k \in B_k \cap C_k$$

$$\forall_j \in U_j \cap C_j$$

$$A_{ij} += B_{ik} C_{kj}$$

Compiling to the streaming dataflow abstract machine

$$\forall_i \in B_i \cap U_i$$



$$\forall_k \in B_k \cap C_k$$





$$\forall_j \in U_j \cap C_j$$

$$A_{ij} += B_{ik} C_{kj}$$

Compiling to the streaming dataflow abstract machine


$$\forall_i \in B_i \cap U_i$$




$$\forall_k \in B_k \cap C_k$$



$$\forall_j \in U_j \cap C_j$$



$$A_{ij} += B_{ik} C_{kj}$$




computation graph
for scalar expression

Inner-product sparse matrix multiplication


hierarchical scanners load coordinates for different tensor dimensions

$$A_{ij} = \sum_k B_{ik} C_{kj}$$




Inner-product sparse matrix multiplication

$$A_{ij} = \sum_k B_{ik} C_{kj}$$




Inner-product sparse matrix multiplication

$$A_{ij} = \sum_k B_{ik} C_{kj}$$




Inner-product sparse matrix multiplication

$$A_{ij} = \sum_k B_{ik} C_{kj}$$



Gustafson sparse matrix multiplication

$$A_{ij} = \sum_k B_{ik} C_{kj}$$




Gustafson sparse matrix multiplication

$$A_{ij} = \sum_k B_{ik} C_{kj}$$

asymptotically more temporary memory, because reduction is into row


asymptotically less work, because intersection occurs earlier



Fused SDDMM

$$A = B \odot (CD)$$

$$O(\text{NNZ}_B \cdot K)$$



Sparse Dataflow Compiler Overview

